


PROUD Streetlight head



Description

Head

For downlighting. Cable meters included: 0.4m. Structure material: High purity aluminium. Structure finish: Urban grey. Diffuser material: Polycarbonate. Diffuser finish: Semitransparent. UV protection. Warranty: 5 Years.

Finish

Urban grey
Semitransparent

Material

High purity aluminium
Polycarbonate



TECHNICAL CHARACTERISTICS

Light source

Light source: LED EDISON
Output (W): 83.5W
Total power consumption (W): 93.5 W
Color temperature: Neutral white - 4000K
CRI: 80
Real Lumen: 6328
Nominal Lumen: 11080
Qty Leds: 342
Lm/Real W: 68
Life Time: 59.000h L70B30
Bin / Grup: 403
MacAdam steps: 2
UGR: 23.7
Photobiological risk: RG0

GEAR

Brand: SOSEN
Gear included: Yes, electronic
Voltage / Frequency: 100-240VAC/50-60Hz
Power Factor: 0.99
Flickering: 2.9%

Luminaire

Double cable exit: No
Drainage: No
Recessed: No
Cable meters included: 0.4m
Uv Protection: Yes
Warranty: 5 Years

Logistics

Energy Efficiency: LED A++
EAN Code: 8435381497309
Net Weight (Kg): 5.940
Weight in Kg (packaged): 7.450
Packing: 480 x 480 x 530
Masterbox: 1

The photograph may not match the reference exactly. Please read the product description to identify the finish.

OPTIONAL ACCESSORIES



55-9305-48-48

Column made of galvanized cast steel. Height of 3.5 m. Suitable for bulbs with a 6 cm diameter entrance. Installation kit includes fixing bolts.

Structure material: Galvanized steel
Dimensions: 300 x 300 x 3500
Net Weight (Kg): 25.000



55-9305-Z5-Z5

This code includes 2 columns.

Structure material: Galvanized steel
Dimensions: 250 x 250 x 3500
Net Weight (Kg): 58.700

